

CALIFORNIA AIR TOOLS 10020DSMAD Powerful 2.0 Hp SMART Ultra Quiet & Oil-Free 10 Gallon Air Compressor with 80% Air Dryer and Automatic Drain Valve




2.0 HP (Rated/Running)
10 Gallon Steel Tank
6.40 CFM @ 40 PSI
5.30 CFM @ 90 PSI
80% Air Drying System
70 Decibel Noise Level

The CALIFORNIA AIR TOOLS 10020DSMAD Ultra Quiet & Oil-Free Air Compressor, with Automatic Drain Valve, is designed to be one of the quietest 2.0 horsepower air compressors in the industry having only 70 decibels of sound.







The SP-9421 Motor/Pump is tested for a minimum pump life of 3000 hours before service. 30% more life before repair. The SP Series of Ultra Quiet Air Compressor Motors have been designed to increase duty cycle and allow for longer continuous run times.*.

ULTRA QUIET

ONLY 70 DB NOISE LEVEL

The Oil-Free Dual Piston Pump System is engineered for high performance and durability.

The CAT-10020SMHAD SMART Air Compressor has an Oil-Free Dual Piston pump designed to have a life cycle before wear of 3000 Plus hours.

The Oil-Free pump allows for use in a variety of temperatures (cold starts) and uneven terrains (no oil in the pump).

The large low profile 10 Gallon Steel Horizontal Air Tank makes storing under a bench, desk, or shelf very easy.

Includes MDR2i OLED Smart Pressure Switch for remote monitoring and control:

The MDR2i OLED Smart Switch may be connected to mobile phones, tablets, notebooks, or computers. The switch can be used as an access point or can be connected to a Wi-Fi network. Compressor features and parameters may be entered and controlled comfortably along with remote monitoring.

Features:

- Programmable ON/OFF Times
- Pressure ON Level (i.e. re-start pressure)
- Pressure OFF Level (i.e. shutdown pressure)
- Unloader Relay Delay: Delay time for activation of the unloader valves during compressor start-up (load reduction).
- Auto Drain Time: Select the time between each drain activation.
- Drain Valve Time: Auto Drain valve opening duration.
- Overcurrent Limit: (i.e. functions as an electrical trip/breaker).
- Pressure Units: Select [bar] or [PSI]

MDR2i OLED Smart Pressure Switch







EZ-1-2301 Auto Drain Valve (with manual drain valve)



Easy Start Valve

Easy Start Valve

Electrical Connectivity



80% Air Dryer







FEATURES

- * Ultra Quiet Only 70 decibels
- * Oil-Free Pump Cleaner air for better tool operation.
- Less maintenance and Costs.
- * Two pressure control gauges
- * One Female Industrial "Push to Connect" quick connector (1/4" NPT)
- * Thermal Overload Protector
- * 125 PSI Maximum Pressure
- * MDR2i OLED Smart pressure switch for remote monitoring and control
- * Kick On Pressure 95 PSI Kick Off Pressure 125 PSI
- * 110v / 60 Hz
- * Low Amp Draw Only 14.0 Amps
- * Tank fill rate from empty to full 130 Seconds
- * Recovery time from 95 PSI to 125 PSI 40 Seconds
- * Duty Cycle 70/30*
- * L (16") x W (23") x H (35")
- * 91 pounds
- * Non-ASME Air Tank
- * Air Dryer Includes Activated Alumina desiccant with a 4000-hour life. Activated Alumina is used in air prepurification (due to its high water and carbon dioxide adsorption capacity) and adsorption of sulphur compounds.
- * Aftercooler (condenser)
- * EZ-1-2321 Auto Drain Valve Factory Installed
- * Commercial Use: Refer to State & City Codes
- * 1 Year Limited Warranty
- * Assembled in USA with global components

For more information and to watch a 10020DSMAD product demonstration please visit California Air Tools: <u>https://www.californiaairtools.com/smart-switch-air-compressors/cat-10020dsmad/</u>



Manufactured in Mexico & USA using global components. MODEL: 10020DSMAD PART NUMBER: CAT-10020DSMAD <u>www.californiaairtools.com</u> Revision A: 12-2024