



FEATURES / SPECS

E250 SERIES

+ OPTIONAL SILENT AIR SYSTEM

TECH SPECS



ESL10V080V1

NOTE: UP TO 50% QUIETER THAN MOST RECIPROCATING PISTON COMPRESSORS. OPERATES AND NORMAL CONVERSATION LEVEL.



SILENCERS SOLD SEPARATELY

SILENTAIR



***REQUIRES TWO QUALIFYING ANNUAL MAINTENANCE KIT PURCHASES

MODEL NUMBER:	ESL07V080Y1	ESL10V080V1
MANUFACTURER:	EMAX	EMAX
TANK SIZE:	80 GALLON	80 GALLON

MOTOR

RUNNING HP:	7.5 HP INDUSTRIAL 1.1 SERVICE FACTOR MOTOR	10 HP INDUSTRIAL 1.1 SERVICE FACTOR MOTOR
VOLTAGE:	230	230
MOTOR RPM:	1740	1740
PHASE:	SINGLE	SINGLE
MAGNETIC STARTER:	YES	YES
MOTOR	OPEN DRIP PROOF	OPEN DRIP PROOF
NUMBER OF BELTS	2	2

PUMP

CFM	25.6 @ 100PSI	38 @ 100PSI
PUMP TYPE:	SPLASH LUBRICATED	SPLASH LUBRICATED
RPMS AT MAX	770	660
MAX PRESSURE:	175 PSI	175 PSI
VALVES	REMOVABLE DISC INDUSTRIAL VALVES	REMOVABLE DISC INDUSTRIAL VALVES
RODS	2 - SOLID STEEL	2 - SOLID STEEL
PUMP LIFE:	50,000	50,000
EXTENDED LIFETIME PUMP WARRANTY	***OPTIONAL	***OPTIONAL

OVERVIEW

CERTIFICATION:	ETL	ETL
DIMENSIONS:	38 x 27 x 71	33 x 42 x 75
PRODUCT WEIGHT:	686 lbs	745 lbs
WARRANTY:	5 YEAR: 1 YR STD, 4 YR EXTENDED	5 YEAR: 1 YR STD, 4 YR EXTENDED
NOISE LEVEL	CONVERSATION LEVEL	CONVERSATION LEVEL
BELT TENSION ADJUSTER	NO	NO
AUTO DRAIN	NO	NO
CONTINUOUS RUN	NO	NO
1 QT OF AIR COMPRESSOR OIL	YES	YES
VIBRATION ISOLATOR PADS (SET)	YES	YES
AIR SILENCER WITH 5 STAGE FIL- TRATION	SOLD SEPARATELY	SOLD SEPARATELY
BELT GUARD	16 GA STEEL	16 GA STEEL