

DW550 SERIES

NEMA4



NEMA 4 RATED WATERPROOF ENCLOSURES ARE ENGINEERED FOR ALL WEATHER APPLICATIONS**

FEATURES & BENEFITS INCLUDE AN ALTERNATING
SWITCH THAT WILL ALLOW THE UNITS TO
ALTERNATE FROM ONE PUMP TO ANOTHER. UNDER
THE NEXT START-UP SEQUENCE THE OPPOSING
PUMP WILL START. THIS ELIMINATES EXCESSIVE
RUNNING AND ALLOWS THE PUMPS TO COOL
UNDER HEAVY LOADS. THESE UNITS ALSO HAVE A
FEATURE THAT IF ONE PUMP WILL NOT MAINTAIN
SET PRESSURE AND NOT KEEPING UP WITH
DEMAND, THEN BOTH UNITS WILL COME ON AND
RUN UNTIL THE UNIT HITS THE PRESSURE SETTING
AFTER WHICH IT WILL GO BACK INTO NORMAL
ALTERNATING MODE

TECH SPECS

| MODEL NUMBER: | EP07DW120V1 |
|--------------------------------------|---|
| MANUFACTURER: | EMAX COMPRESSOR |
| TANK SIZE: | 120 GALLON |
| MOTOR | |
| RUNNING HP: | *(2) 7.5HP NEMA 4 Industrial 1.2 Service Factor |
| VOLTAGE: | 230 |
| MOTOR RPM: | 1740 |
| PHASE: | SINGLE |
| MAGNETIC STARTER: | YES |
| MOTOR | TEFC |
| NUMBER OF BELTS | 4 |
| РИМР | |
| PUMP TYPE: | 2 STAGE SOLID CAST IRON |
| RPMS AT MAX | 640 |
| MAX PRESSURE: | 175 PSI |
| VALVES | REMOVABLE DISC IN- DUSTRIAL VALVES |
| RODS | 2 - SOLID STEEL |
| PUMP LIFE: | 60,000 |
| EXTENDED LIFETIME | ***OPTIONAL |
| PUMP WARRANTY | |
| OVERVIEW | |
| CERTIFICATION: | ETL |
| DIMENSIONS: | 96 X 42 X 64 |
| PRODUCT WEIGHT: | 550lbs |
| WARRANTY: | 5 YEAR: 1 YR STD, 4 YR EXTENDED |
| NOISE LEVEL - DBA | NOT RATED |
| BELT TENSION ADJUSTER | YES |
| AUTO DRAIN | YES |
| CONTINUOUS RUN | NO |
| 1 QT OF AIR COMPRESSOR OIL | YES |
| VIBRATION ISOLATOR PADS (SET) | YES |
| AIR SILENCER WITH 5 STAGE FILTRATION | YES |
| BELT GUARD | 16 GAUGE STEEL |
| | |

^{*15}HP WHEN BOTH MOTORS AND PUMPS ARE OPERATING SIMULTANEOUSLY

^{**}INDOOR & OUTDOOR

^{***}REQUIRES TWO QUALIFYING ANNUAL MAINTENANCE KIT PURCHASES